

Part Number	Inductance L(μ H) @ 1.0 KHz	DC Resistance (Ohms)	SRF (MHz) Typ	DC Current (Amps)	Dimensions (mm)			
					A ± 0.3	B ± 0.3	C ± 0.3	Reel QTY
MDRS-1205-101TK	100	0.25	7	1.05	12.6	11.6	5.4	500
MDRS-1205-121TK	120	0.28	6	0.95	12.6	11.6	5.4	500
MDRS-1205-151TK	150	0.40	6	0.85	12.6	11.6	5.4	500
MDRS-1205-181TK	180	0.48	5	0.77	12.6	11.6	5.4	500
MDRS-1205-221TK	220	0.52	5	0.70	12.6	11.6	5.4	500
MDRS-1205-271TK	270	0.70	4	0.63	12.6	11.6	5.4	500
MDRS-1205-331TK	330	0.80	4	0.57	12.6	11.6	5.4	500
MDRS-1205-391TK	390	1.08	4	0.52	12.6	11.6	5.4	500
MDRS-1205-471TK	470	1.20	3	0.48	12.6	11.6	5.4	500
MDRS-1205-561TK	560	1.34	3	0.44	12.6	11.6	5.4	500
MDRS-1205-681TK	680	1.78	3	0.40	12.6	11.6	5.4	500
MDRS-1205-821TK	820	2.00	2	0.36	12.6	11.6	5.4	500

GENERAL PARAMETERS: Layout, Schematic, Packaging

